

Specifications

HPE ProLiant DL160 Gen10 (G10) Server - Specifications

PROCESSOR - 2 SOCKETS

- 2x Intel Xeon Scalable Silver 4110 processor
- 2x Intel Xeon Scalable Bronze 3106 processor

OPERATING SYSTEM

- Windows Server 2012 R2 (Most Recent Version)
- Windows Server 2016 (Most Recent Version)
- VMware ESXi 6.0 U3
- VMware ESXi 6.5 and U1 upon release
- Red Hat Enterprise Linux (RHEL) 6.9 and 7.3
- SUSE Linux Enterprise Server (SLES) 11 SP4 and 12 SP2
- ClearOS
- CentOS

CHIPSET

Intel C621

MEMORY

Each processor supports up to 8 memory modules in six memory channels
Memory speeds of 2133MT/s or 2400Mhz depending on processors

STORAGE

Configurations:

- 4 x 3.5-inch drives
- 8 x 2.5-inch drives
- Optional media bay to house either an optical devices or an addition 2 2.5-inch drives

STORAGE CONTROLLER

- SmartArray RAID Controller

NETWORK DAUGHTER CARDS

Unavailable

MANAGEABILITY

- HPE iLO Standard
- Advanced Premium Security Edition (purchase necessary)

I/O PORTS

Front:

- iLO Service Port

- USB 3.0

Rear:

- 2 x USB3.0
- Video port
- iLO Management Port
- 2 x NIC Ports
- Serial port (optional)

Internal:

- Micro SD Card slot
- TPM Connector
- Serial port connector
- 3 x Mini-SAS ports
- USB 3.0

CHASSIS

1U Rack

BAYS

- 4 Bay LFF
- 8 Bay SFF
- 10 Bay SFF

OPTICAL DRIVE

- Optional Optical drive
- Optional media bay (optical drive, SFF SAS/SATA, or NVMe)

POWER

2 x 500W power supplies
80 PLUS® Platinum

SECURITY OPTIONS

Optional:

- Advanced Premium Security