

Wyse 5470 All-in-One Thin Client

Base

- Wyse 5470 AIO, FBTX

Operating System

- PCoIP enabled Wyse ThinOS 8.6, English, includes Wyse ThinOS Firmware Access

Display

- Wyse 5470 All-in-One Non-Touch Camera FHD LCD 24" Panel

Processor

- Intel Celeron™ J4105 (4 Cores/4MB/4T/up to 2.5GHz/10W) supports Windows10/Linux/ThinOS/ThinOS+PcoIP

Power

- External 90 Watt Power Adapter. 4.5mm barrel

Port USB

- 4 USB 3.0 (2 side and 2 rear)
2 USB 2.0 (rear, 1 smart power on)
1 DisplayPort™ 1.2a (rear)
1 Global Headset Jack (rear)
1 Stereo Line Out (side)
1 RJ-45 (rear)
1 Power Connection (rear)

Memory

- 4GB 1x4GB, 2400MHz DDR4 Memory

Hard Drive

- 16GB eMMC Included in Chassis

Dimension & Weight

- Height: 15.17" (385.33mm) x Width: 22.7" (576.62mm) x Depth: 2.12" (54mm)
Weight with easel stand: 12.56 lb (5.7kg)ⁱ

Warranty

- 3 Years ProSupport with Next Business Day Onsite Services

Slots

- 1 Chassis Lock Slot Support

Chassis

- Front Bezel and back cover - Plastic Black Resin

Regulatory

- Regulatory model: N2A
Regulatory Type: N2A001
Environmental Standards (eco-labels)
ENERGY STAR qualified
EPEAT Registered *
WEEE *
TAA Configurations Available
Halogen free, except EPS